



TWEETERS


- 4-8 ohm Impedance
- Power Handling: 200 watts peak / 100 watts rms
- Frequency Response: 5kHz-25kHz
- Sensitivity: 102db (1W / 1m)

DES KITS DE LA GAMME

- Impédance du système 4-8 ohms
- Puissance Admissible: 200 watts peak / 100 watts rms
- Réponse de fréquence: 5kHz-25kHz
- Sensibilité: 102db (1W / 1m)

SISTEMA COMPONENTE BIDIRECCIONAL DEL ALTAVOZ

- Impedancia del Sistema 4-8 ohms
- Manejo de Potencia: 200 watts peak / 100 watts rms
- Respuesta de Frecuencia: 5kHz-25kHz
- Sensibilidad: 102db (1W / 1m)



- A Surface Mount Fixture Diameter**
1 5/16" / 33 mm
- B Surface Mount Protrusion**
3/4" / 19 mm

WATTS: Peak Power is an instantaneous measurement that occurs sporadically during musical peaks. RMS Power is a measurement of continuous power without damage from heat generated by the voice coil or excessive mechanical excursion. Ref: EIA-426B (USA)

S-12T

PowerBass® AutoSound (PB) – A division of PowerBass® USA, Inc.
13936 Mountain Avenue, Chino, CA 91710
Tel: (909) 993-5399 Fax: (909) 993-5393 www.powerbassusa.com



Warranty may be void if serial no. is removed

UPC



This manual is the exclusive property of PowerBass® USA, Inc. Any reproduction of this manual, or use other than its intentions is strictly prohibited without the express consent of PowerBass® USA, Inc. © Copyright 2006 PowerBass® USA, Inc.

Due to continuing product improvement, features and specifications are subject to change without notice.